
# MANTARTIS







## The advantages of Fog 40

The pump installed works without valves, without plungers, without seals, and without oil Equipped with 4 support feet and a handle to facilitate moving, and it also can be hung on the wall without using shelves Remote control with a range of 30m Maintenance costs reduced by 80%

## TECHNICAL DATA

CODE	Model	No. of nozzles	Pressure	Flow rate	Power	Weight	Dimensions WxLxH (mm)
ZX.8062	Fog 40-70	min 10-max 35*	40bar	70l/h	375W, 230V- 50Hz	15kg	250x390x210
ZX.8063	Fog 40- 150	min 25-max 75*	40bar	150l/h	700W, 230V- 50Hz	18kg	250x390x210

<sup>\*</sup> The maximum number of nozzles has been calculated using a nozzle with flow rate 0,151/min. (MT.154C-RB4)

FAST AND PRECISE CONTROL ALWAYS HANDY

## HIGHLIGHTS







## FOG 40 CONTROLS

# TECHNICAL DATA

Frame made of powder painted galvanized plate
Motor-pump 1450Rpm, 230V-50Hz with volumetric vane pump

L.p. solenoid valve 230V-50Hz. inlet water

L.p. pressure switch for lack of water

devices (level sensors, fans, UV lamps, lights)

## STANDARD EQUIPMENT

m range 30m with 4 channels, preset with pump on/off key, light switch-on/off, and combined switch-on/off of pump and fans

**FOG 40**