



HIGHLIGHTS



BUILT-IN ANALOGUE TIMER

Pause from 0 to 60 seconds
work from 0 to 60 seconds

OPTIONALS / ZX.5095



ZX.KF5090

Inlet water filter kit, 5", G 1/2"
M-F complete with 5micron
polypropylene cartridge

TECHNICAL DATA

Frame made of galvanised plate
Motor-pump 1420Rpm, 230V-50Hz with axial pump 2 plungers
Thermal protection against current surge
Built-in analogue timer, pause from 0 to 60 seconds/work from 0 to 60 seconds
 Unloader valve
 L.p. pressure switch for lack of water
 Automatic anti-drip system
 Dimensions WxLxH: 41 x 26 x 26mm

TECHNICAL DATA

CODE	Model	No. of nozzles	Pressure	Flow rate	Power absorption	Weight
ZX.5090	FOG ECO 1	22*	60bar	0,9l/min	200W (1x230V-50Hz)	15kg
ZX.5095	FOG ECO 05	11*	60bar	0,5l/min	200W (1x230V-50Hz)	15kg

*The maximum number of nozzles has been calculated using a nozzle with flow rate 15 (0,042l/min) at 60bar

FOG 60 ECO1

ΠΙΕΣΤΙΚΟ ΣΥΓΚΡΟΤΗΜΑ 60 BAR