



Fog nozzle with anti-drip valve thread 10/24UNC/2A



Code Flow rate factor

MT.154C	15
MT.204C	20
MT.304C	30
MT.404C	40
MT.504C	50
MT.604C	60
MT.804C	80
MT.1004C	100

PC.KXC-01

Nickel-plated brass
adapter, swivel
type, threaded
10/24UNC/2A M-F



PC.NL360

Nickel-plated brass
adapter, 4 holes,
threaded, inlet
10/24UNC/2A M outlet
4x10/24UNC/2A F



Flow rate table

Flow rate factor Nozzle	7bar	14bar	21bar	28bar	35bar	42bar	56bar	70bar	84bar	100bar	120bar	
15	x	x	x	0,029	0,033	0,036	0,041	0,046	0,051	0,059	0,074	l/min
20	x	x	0,049	0,056	0,063	0,069	0,080	0,089	0,098	0,101	0,114	l/min
30	x	0,065	0,08	0,092	0,103	0,113	0,130	0,145	0,159	0,166	0,176	l/min
40	0,056	0,08	0,098	0,113	0,126	0,138	0,159	0,178	0,195	0,201	0,215	l/min
50	0,077	0,109	0,134	0,154	0,172	0,189	0,218	0,248	0,267	0,275	0,301	l/min
60	0,101	0,143	0,175	0,202	0,226	0,248	0,286	0,302	0,351	0,361	0,388	l/min
80	0,138	0,195	0,238	0,275	0,308	0,337	0,389	0,435	0,477	0,491	0,527	l/min
100	0,178	0,252	0,308	0,355	0,398	0,436	0,503	0,553	0,617	0,635	0,670	l/min